

GARONCRYLIC™

Outdoor Deck Coating



PRODUCT DESCRIPTION:

GARONCRYLIC™ is a liquid applied water based, urethane modified, acrylic industrial maintenance coating. GARONCRYLIC has very little odor and very low VOC content. It is an economical light to medium

duty deck topcoat with excellent weathering and UV resistance, coupled with excellent hiding capabilities. Can be used to re-seal and color existing cover layers that have become faded, stained or discolored. Can also be used to top back to cover all types of existing systems of the cover layer as acrylics, epoxies and urethanes.

FEATURES & BENEFITS:

- Single-component application
- Excellent weathering & UV resistance properties
- High hiding with one coat application
- Easy, cost saving application

LIMITATIONS

Do not apply to hot surface or during unusually hot weather or streaking or sticky condition may result. Do not apply in temperatures below 55°F or above 90°F. Avoid applying GARONCRYLIC™ in hot weather in direct sunlight. Do not apply if rain is anticipated before the coating can adequately dry. Not designated for vehicular traffic.

SHELF LIFE

Twelve (12) months after manufacture when continuously stored indoors in unopened pails at temperatures under 80°F. Stir thoroughly prior to use.

STANDARD COLORS

Storm Gray.

INSTALLATION

Surface Preparation: All surfaces must be cleaned and free of all foreign matter such as dirt, oil and grease. High pressure water washing with a mild detergent is recommended. Proper cleaning is mandatory for GARONCRYLIC™ to bond properly to the substrate.

APPLICATION

With a brush, roller or spray equipment, apply GARONCRYLIC™ at 125-150 square feet per gallon per coat. Depending on the surface condition and the aggregate size, 2 coats are almost always recommended. 2 light coats always work better than 1 heavy coat. Depending on air temperature, allow to sufficiently dry (usually 4-8 hours) before light foot traffic is allowed. Do not place heavy objects on the surface or put patio furniture on the surface until after at least 96 hours of warm weather curing. CAUTION: The application of GARONCRYLIC™ over some surfaces may cause the surface to become slippery when wet. In these situations, light aggregate should be added to and backrolled into the GARONCRYLIC™ to aid in slip resistance.

PRECAUTIONS

Before using this product, read the container precautionary label and the SDS data sheet carefully. Do not get into eyes, onto skin, or clothing. If contact occurs, flush affected areas with soap and water. Wash clothing before reuse. Use only with adequate ventilation. Seek medical help for all-over exposures. THIS PRODUCT IS FOR PROFESSIONAL USE ONLY.

CURE SCHEDULE (typical)

Tack Free (dry to touch).....1-4 hours
Recoat or Topcoat.....3-6 hours
Light Foot Traffic.....4-8 hours
Normal Use.....4-7 days

MIX RATIO BY VOLUME:

One component – mix well before using.

COVERAGE, Sq. Ft./Gal

125-150 square feet/gallon (10-12 mils typical).

VOC CONTENT

<50 g/L

TECHNICAL DATA

Property	Typical Value	Test Method
Bond Strength to plywood	130 psi	ASTM C-297
Water Vapor Perm Eability	2.3 perm s	ASTM E-96
Impact Test	No cracking	ASTM C-3320
Freeze/Thaw	No change	ASTM C-67
Weatherometer (2,000 hours)	No degradation	ASTM G-23
Elongation	125%	ASTM D-2370
Tensile Strength	1000 psi	ASTM D-412



NOTICE TO BUYER:

DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT.** We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may **CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET AND FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.**